



REV A January 2011

Oscilent Controlled Document

Ordering Code / Part Number	Product Description
813-SL128.0625M-02A	28.0625 MHz IF SAW Filter 1.875 MHz Bandwidth

Specification Contents

- o Mechanical Dimensions
- o Test Circuit
- o Maximum Ratings
- o Electrical Specification
- o Frequency Response
- o Smith Chart
- o VSWR

Notes

- o Electrostatic Sensitive Device (ESD) 
- o Avoid excessive ultrasonic exposure
- o Solderability compatible with JEDEC J-STD-020C Pb-free process, 260°C peak reflow temperature
- o This product complies with EU directive 2002/95/EC (RoHS compliance)






Mechanical Dimensions (mm)



Pin Description	
A, B, C, D, F, G, H, I, J, L	Ground
K	Input
E	Output

Test Circuit



Test Fixture & Values	
Input	L1=100 nH, C1=27pF
Output	L2=82 nH, C2=43pF
Source/Load Impedance	50 Ω



Maximum Ratings

Parameters Description	Unit	Minimum	Typical	Maximum
Operating Temperature Range	°C	0	-	60
Storage Temperature Range	°C	-20	-	70
Maximum DC Voltage	V	-	-	10
Maximum Input Power	dBm	-	-	10
Source Impedance (single ended) ⁽¹⁾	Ω	-	50	-
Load Impedance (single ended) ⁽¹⁾	Ω	-	50	-

Notes: With Matching Network (Ref. Testing Environment Circuit as shown above).

Those impedances could be modified with different impedance values and/or structures, if necessary.


Electrical Specification

Parameters Description	Unit	Minimum	Typical	Maximum
Center Frequency (Fo)	MHz	127.9625	128.0625	128.1625
Insertion Loss at Fo	dB	-	20.0	24.0
Group Delay Variation (Fo±0.9375MHz)	nsec	-	60	120
Absolute Delay	usec	-	1.72	-
Temperature Coefficient	ppm/°C	-	-0.03	-
Passband Ripple (Fo±0.9375MHz)	dB	-	0.4	1.00
Bandwidth at -1dB	MHz	1.875	2.24	-
Bandwidth at -30dB	MHz	-	3.71	-
Bandwidth at -40dB	MHz	-	3.89	4.50
Ultimate Rejection	dB	48	53	-
Relative Attenuation Fo±2.1625MHz	dB	30	60	-




Frequency Response


Bandwidth at -3.0 dB




Bandwidth at -40.0 dB



Bandwidth at -1.0 dB




Relative Attenuation Fo±2.1625MHz







Ripple Variation Fo±0.9375MHz



Group Delay Variation Fo±0.9375MHz



Smith Chart





VSWR

