



PRODUCT SPECIFICATION

REV A January 2011

Oscilent Controlled Document

Ordering Code / Part Number	Product Description
813-SL62.5M-19E	62.5MHz IF SAW Filter 19.18MHz Bandwidth

Specification Contents

- o Mechanical Dimensions
- o Test Circuit
- o Maximum Ratings
- o Electrical Specification
- o Frequency Response
- o Smith Chart
- o VSWR

Notes

- o Electrostatic Sensitive Device (ESD) 
- o Avoid excessive ultrasonic exposure
- o Solderability compatible with JEDEC J-STD-020C Pb-free process, 260°C peak reflow temperature
- o This product complies with EU directive 2002/95/EC (RoHS compliance)



Oscilent Corporation
Telephone: 1.949.252.0522
Fax: 1.949.252.0522
Email: sales@oscilent.com




Mechanical Dimensions (mm)



Pin Description	
A, B, C, D, F, G, H, I, J, L	Ground
K	Input
E	Output

Test Circuit



Test Fixture & Values	
Input	L1=150nH, C1=36pF
Output	L2=27nH, L3=100pF
Source/Load Impedance	50 Ω



Maximum Ratings

Parameters Description	Unit	Minimum	Typical	Maximum
Operating Temperature Range	°C	-20	-	70
Storage Temperature Range	°C	-40	-	85
Maximum DC Voltage	V	-	-	10
Maximum Input Power	dBm	-	-	10
Source Impedance (single ended) ⁽¹⁾	Ω	-	50	-
Load Impedance (single ended) ⁽¹⁾	Ω	-	50	-

Notes: With Matching Network (Ref. Testing Environment Circuit as shown above).

Those impedances could be modified with different impedance values and/or structures, if necessary.


Electrical Specification

Parameters Description	Unit	Minimum	Typical	Maximum
Center Frequency (Fo)	MHz	62.4	62.5	62.6
Insertion Loss at Fo	dB	-	14.7	16.0
Temperature Coefficient	ppm/°C	-	-86	-
Amplitude Ripple within fo ±9.22 MHz	dB _{p-p}	-	0.45	0.80
Group Delay Variation within fo ±9.22 MHz	nsec	-	45	60
Absolute Delay at Fo	µsec	-	1.11	-
Bandwidth at -1.0 dB	MHz	-	19.18	-
Bandwidth at -15.0 dB	MHz	-	21.40	-
Bandwidth at -40.0 dB	MHz	-	23.10	24.0
Relative Attenuation:				
Lower Sidelobe	dB	45	48	-
Upper Sidelobe	dB	45	48	-




Frequency Response

Bandwidth at -1.0 dB




Bandwidth at -15.0 dB



Bandwidth at -40.0 dB




Wide-Band







Ripple Variation Fo±9.22MHz



Group Delay Variation Fo±9.22MHz



Smith Chart





VSWR

