



PRODUCT SPECIFICATION

REV A January 2011


Oscilent Controlled Document

Ordering Code / Part Number	Product Description
813-SL75.0M-27D	75.0 MHz IF SAW Filter 27.15 MHz Bandwidth

Specification Contents

- o Mechanical Dimensions
- o Test Circuit
- o Maximum Ratings
- o Electrical Specification
- o Frequency Response
- o Smith Chart
- o VSWR



Notes

- o Electrostatic Sensitive Device (ESD) 
- o Avoid excessive ultrasonic exposure
- o Solderability compatible with JEDEC J-STD-020C Pb-free process, 260°C peak reflow temperature
- o This product complies with EU directive 2002/95/EC (RoHS compliance)






Mechanical Dimensions (mm)



Pin Description	
A, B, C, D, F, G, H, I, J, L	Ground
K	Input
E	Output

Test Circuit



Test Fixture & Values	
Input	L1 = 68 nH
Output	L2 = 8.2 nH, L3 = 82 nH
Source/Load Impedance	50 Ω



Maximum Ratings

Parameters Description	Unit	Minimum	Typical	Maximum
Operating Temperature Range	°C	-	25	-
Storage Temperature Range	°C	-40	-	85
Maximum DC Voltage	V	-	-	10
Maximum Input Power	dBm	-	-	10
Source Impedance (single ended) ⁽¹⁾	Ω	-	50	-
Load Impedance (single ended) ⁽¹⁾	Ω	-	50	-

Notes: With Matching Network (Ref. Testing Environment Circuit as shown above).

Those impedances could be modified with different impedance values and/or structures, if necessary.


Electrical Specification

Parameters Description	Unit	Minimum	Typical	Maximum
Center Frequency (Fo)	MHz	-	75.0	-
Insertion Loss at Fo	dB	-	14.5	16.0
Group Delay Variation at Fo ± 12.48 MHz	nsec	-	20	50
Absolute Delay at Fo	usec	-	1.10	-
Passband Ripple Variation at Fo ± 12.48 MHz	dB	-	0.3	0.8
Bandwidth at -1dB	MHz	-	27.15	-
Bandwidth at -3dB	MHz	27.50	27.92	-
Bandwidth at -15dB	MHz	-	29.63	30.00
Bandwidth at -40dB	MHz	-	31.38	-
Ultimate Rejection	dB	40	47	-
Temperature Coefficient	ppm/°C	-	-86	-




Frequency Response


Bandwidth at -1.0 dB




Bandwidth at -3.0 dB



Bandwidth at -15.0 dB




Bandwidth at -40.0 dB







Ripple Variation Fo±12.48MHz



Group Delay Variation Fo±12.48MHz



Smith Chart





VSWR

