



REV A January 2011

Oscilent Controlled Document

Ordering Code / Part Number	Product Description
820-IF122.5M-19A	122.5MHz IF SAW Filter 19.09MHz Bandwidth

### Specification Contents

- o Mechanical Dimensions
- o Test Circuit
- o Maximum Ratings
- o Electrical Specification
- o Frequency Response
- o Smith Chart
- o VSWR


### Notes

- o Electrostatic Sensitive Device (ESD) 
- o Avoid excessive ultrasonic exposure
- o Solderability compatible with JEDEC J-STD-020C Pb-free process, 260°C peak reflow temperature
- o This product complies with EU directive 2002/95/EC (RoHS compliance)






## Mechanical Dimensions (mm)



Pin Description	
B, C, D, F	Ground
A	Input
E	Output

## Test Circuit



Test Fixture & Values	
Input	L1= 56 nH, C1=30 pF
Output	L2= 150 nH
Source/Load Impedance	50 $\Omega$



## Maximum Ratings

Parameters Description	Unit	Minimum	Typical	Maximum
Operating Temperature Range	°C	-20	-	70
Storage Temperature Range	°C	-40	-	85
Maximum DC Voltage	V	-	-	10
Maximum Input Power	dBm	-	-	10
Source Impedance (single ended) <sup>(1)</sup>	Ω	-	50	-
Load Impedance (single ended) <sup>(1)</sup>	Ω	-	50	-

Notes: With Matching Network (Ref. Testing Environment Circuit as shown above).

Those impedances could be modified with different impedance values and/or structures, if necessary.


## Electrical Specification

Parameters Description	Unit	Minimum	Typical	Maximum
Center Frequency (Fo)	MHz	122.40	122.50	122.60
Insertion Loss at Fo	dB	-	22.00	24.00
Amplitude Ripple Variation	dB <sub>p-p</sub>	-	0.6	1.0
Group Delay Variation	nsec	-	39	70
Absolute Delay at Fo	μsec	-	2.19	-
Bandwidth at -1.0 dB	MHz	-	19.09	-
Bandwidth at -3.0 dB	MHz	19.30	19.40	-
Bandwidth at -40.0 dB	MHz	-	20.83	21.00
Relative Attenuation				
Lower Sidelobe	dB	50	55	-
Upper Sidelobe	dB	50	55	-
Temperature Coefficient	ppm/°C	-	-72	-




## Frequency Response


### Bandwidth at -1.0 dB




### Bandwidth at -3.0 dB



### Bandwidth at -40.0 dB




### Bandwidth at -50.0 dB







### Ripple Variation at $F_o \pm 9.15$ MHz



### Group Delay Variation at $F_o \pm 9.15$ MHz



### Smith Chart





### VSWR

