



REV A January 2011

Oscilent Controlled Document

Ordering Code / Part Number	Product Description
820-IF252.5M-30A	52.5 MHz IF SAW Filter 30.21 MHz Bandwidth

Specification Contents

- o Mechanical Dimensions
- o Test Circuit
- o Maximum Ratings
- o Electrical Specification
- o Frequency Response
- o Smith Chart
- o VSWR


Notes

- o Electrostatic Sensitive Device (ESD) 
- o Avoid excessive ultrasonic exposure
- o Solderability compatible with JEDEC J-STD-020C Pb-free process, 260°C peak reflow temperature
- o This product complies with EU directive 2002/95/EC (RoHS compliance)






Mechanical Dimensions (mm)



Pin Description	
B, C, D, F	Ground
A	Input
E	Output

Test Circuit



Test Fixture & Values	
Input	L1 = 8.2 nH, C1 = 180 pF
Output	L2 = 10 nH, C2 = 130 pF
Source/Load Impedance	50 Ω



Maximum Ratings

Parameters Description	Unit	Minimum	Typical	Maximum
Operating Temperature Range	°C	-20	-	70
Storage Temperature Range	°C	-40	-	85
Maximum DC Voltage	V	-	-	10
Maximum Input Power	dBm	-	-	10
Source Impedance (single ended) ⁽¹⁾	Ω	-	50	-
Load Impedance (single ended) ⁽¹⁾	Ω	-	50	-

Notes: With Matching Network (Ref. Testing Environment Circuit as shown above).

Those impedances could be modified with different impedance values and/or structures, if necessary.


Electrical Specification

Parameters Description	Unit	Minimum	Typical	Maximum
Center Frequency (Fo)	MHz	-	252.5	-
Insertion Loss at Fo	dB	-	30.0	-
Group Delay Variation at Fo ± 14.52 MHz	nsec	-	36	80
Absolute Delay at Fo	usec	-	2.86	-
Passband Ripple Variation at Fo ± 14.52 MHz	dB	-	0.68	1.0
Bandwidth at -1dB	MHz	29.95	30.21	-
Bandwidth at -3dB	MHz	-	30.48	-
Bandwidth at -40dB	MHz	-	31.78	31.95
Bandwidth at -50dB	MHz	-	31.98	-
Ultimate Rejection	dB	50	55	-
Temperature Coefficient	ppm/°C	-	-18	-




Frequency Response


Bandwidth at -1.0 dB




Bandwidth at -3.0 dB



Bandwidth at -40.0 dB




Bandwidth at -50.0 dB







Ripple Variation Fo±14.52MHz



Group Delay Variation Fo±14.52MHz



Smith Chart





VSWR

