



REV A January 2011

Oscilent Controlled Document

Ordering Code / Part Number	Product Description
867-SL135.0M-07B	135.0 MHz IF SAW Filter 7.8 MHz Bandwidth

### Specification Contents

- o Mechanical Dimensions
- o Test Circuit
- o Maximum Ratings
- o Electrical Specification
- o Frequency Response

### Notes

- o Electrostatic Sensitive Device (ESD) 
- o Avoid excessive ultrasonic exposure
- o Solderability compatible with JEDEC J-STD-020C Pb-free process, 260°C peak reflow temperature
- o This product complies with EU directive 2002/95/EC (RoHS compliance)







## Maximum Ratings

Parameters Description	Unit	Minimum	Typical	Maximum
Operating Temperature Range	°C	-40	-	85
Storage Temperature Range	°C	-40	-	85
Maximum DC Voltage	V	-	-	10
Maximum Input Power	dBm	-	-	10
Source Impedance (single ended) <sup>(1)</sup>	Ω	-	50	-
Load Impedance (single ended) <sup>(1)</sup>	Ω	-	50	-

Notes: With Matching Network (Ref. Testing Environment Circuit as shown above).

Those impedances could be modified with different impedance values and/or structures, if necessary.

## Electrical Specification

Parameters Description	Unit	Minimum	Typical	Maximum
Center Frequency (Fo)	MHz	-	135.0	-
Insertion Loss at Fo	dB	-	17.0	19.0
Amplitude Ripple Variation	dB <sub>p-p</sub>	-	0.5	1.0
Group Delay Variation at Fo ± 3.5 MHz	nsec	-	45	90
Absolute Delay at Fo	μsec	-	0.76	-
Temperature Coefficient	ppm/°C	-	-23	-
Bandwidth at -1.0 dB	MHz	7.5	7.8	-
Bandwidth at -3.0 dB	MHz	8.4	8.6	-
Bandwidth at -40.0 dB	MHz	-	12.5	12.8
Relative Attenuation				
Lower Sidelobe	dB	40	45	-
Upper Sidelobe	dB	40	45	-



## Frequency Response

