



REV A January 2010

Oscilent Controlled Document

Ordering Code / Part Number	Product Description
802-RF881.5M-D	CDMA, RF-Rx SAW Filter

Specification Contents

- o Mechanical Dimensions
- o Test Circuit
- o Maximum Ratings
- o Electrical Specification
- o Frequency Performance
- o VSWR
- o Smith Chart


Notes

- o Electrostatic Sensitive Device (ESD) 
- o Avoid excessive ultrasonic exposure
- o Solderability compatible with JEDEC J-STD-020C Pb-free process, 260°C peak reflow temperature
- o This product complies with EU directive 2002/95/EC (RoHS compliance)







Mechanical Dimensions (mm)



Pin Description	
A, C, D, F	Ground
E	In
B	Out



Test Circuit



Source and Load Impedance: 50 Ω



Maximum Ratings

Parameters Description	Unit	Minimum	Typical	Maximum
Operating Temperature Range	°C	-30	-	+80
Storage Temperature Range	°C	-40	-	+85
Maximum DC Voltage	V	-	-	5
Maximum Input Power	dBm	-	-	15
Source Impedance (single ended) ⁽¹⁾	$\Omega//pF$	-	50	-
Load Impedance (single ended) ⁽¹⁾	$\Omega//pF$	-	50	-



Notes: No Matching Network (Ref. Testing Environment Circuit as shown above).

Electrical Specification

Parameters Description	Unit	Minimum	Typical	Maximum
Center Frequency (Fo)	MHz	-	881.5	-
Insertion Loss within 869~894MHz	dB	-	2.2	3.0
Amplitude Ripple within 869~894MHz	dB _{p-p}	-	0.6	1.5
Attenuation:				
D.C. ~ 779 MHz	dB	50	60	-
779 ~ 849 MHz	dB	42	47	-
914 ~ 970 MHz	dB	26	30	-
970 ~ 1049 MHz	dB	50	58	-
1049 ~ 2000 MHz	dB	45	55	-
VSWR within 869~894MHz	-	-	1.6	2.0





Frequency Performance





VSWR



Smith Chart

